



Product Catalog


Performances and products



Glass window



Glass doors




Glass façade



Security and
Thermochromic glass




Burglar resistance



Ballistic resistance



Fire Rated



Blast resistance

Capabilities & Certifications

System Type	Capabilities	Verified standards
Fire Rated	EI60-EI120 (EI240 Testing in Progress)	EN1364-3 EN1634-1
Ballistic-Resistant	FB2-FB7 (BR2 NS – BR7 NS), UL 752 Level 1-7, NIJ 0108.01 Type I-III	EN 1063, EN 1522-1523, UL 752, NIJ 0108.01
Burglar-Resistant	RC3-RC6 (P5A-P8B)	EN 356, EN1627-1630
Blast-Resistant	Up to EXR3 / GSA Level C	EN 13123-2, ISO 16933, GSATS01

System Building Physics



thermal insulation
 $u=1.0-1.5 \text{ w/(m}^2\cdot\text{k)}$



resistance against hurricane
 $\geq 16 \text{ kpa/m}^3 \text{ (1800*1500)}$



water tightness
 $\geq 700 \text{ pa}$



air permeability
length of seam: $\leq 0.5 \text{ m}^3 \text{ (m}\cdot\text{h)}$
square: $\leq 1.4 \text{ m}^2 \text{ (m}\cdot\text{h)}$



sound insulation
 $\geq 44 \text{ dB(A)}$

Contact us

Headquarters:

HWARRIOR PTE LTD (Singapore)

Address: #08-01 101 Eunos Ave 3, S409835

Mobile/WhatsApp: +65 8939 6836

Email: req@kingforts.com

Website: <http://www.kingforts.com>

